



2019 200 RR 2-Stroke

## Engine

Type:	Beta-Built single cylinder, 2-stroke, liquid cooled, with BPV power valve system and <u>electric start</u> with a back up kick starter sold as an option.
Bore:	62mm
Stroke:	63mm
Displacement:	190.2cc
Compression Ratio:	13.5:1
Exhaust Valve	Beta Progressive Valve (BPV)
Ignition:	AC-CDI Kokusan
Spark Plug:	NGK BR8ECM
Lubrication:	Electronic Oil Injection
Oil Tank Capacity	650cc
Carburetor:	Keihin PWK 36mm
Clutch:	Wet multi-disc
Transmission:	6-speed
Final Drive:	O-ring chain

## Chassis

Frame:	Molybdenum steel/double cradle w/quick air filter access.
Wheelbase:	58.1"
Seat Height:	36.6"
Ground Clearance:	12.8"
Footrest Height:	16.1"
Dry Weight:	215 lbs. (wet weight, no fuel)
Fuel Tank Capacity:	2.25 US gallons
Front Suspension:	48 mm Sachs USD fork, adjustable compression, rebound, & spring preload.
Rear Suspension:	Aluminum Body Sachs shock w/adjustable rebound and hi/low speed compression
Front Wheel Travel:	11.6"
Rear Wheel Travel:	11.4"
Front Brake:	260mm rotor
Rear Brake:	240mm rotor
Front/Rear Rim:	21" (Front) 18" (Rear)
Front/Rear Tire:	Enduro Competition
Warranty:	6 month Limited Warranty
MSRP:	<b>\$8399.00</b>

\*Specifications subject to change without notice. Additional information on all models including manuals, accessories and parts books are available online at [www.betausa.com](http://www.betausa.com) under support.

