STT-2023-1 JULY 8, 2024



Service Tech Tip KYB Fork Set Up

Model: KYB AOS Front Fork

ADJUSTMENT KEY:

RED = FACTORY SETTINGS BLUE = RACING RECOMMENDATIONS GREEN = COMFORT RECOMMENDATIONS PURPLE = SOFT RECOMENDATIONS

2023-24' 125/200 Race Edition

125/200 Race Edition Fork Adjustment

Fork Spring Rate .42 kg Oil level 300 cc Pressure spring Rate 2.1 kg Compression = 14 out 10 14 16 Rebound = 14 out 12 14 16

125/200 Race Shock Adjustment

Shock Spring Rate 4.9 kg
Static Sag Range 25-45mm
Rider Sag Range 95-110mm

Low Speed Compression = 15 out 7 12 15
High Speed Compression = 1.5 turns out 1.25 1.5 1.75
Rebound = 13 out 7 9 12

ADJUSTMENT KEY:

RED = FACTORY SETTINGS BLUE = RACING RECOMMENDATIONS GREEN = COMFORT RECOMMENDATIONS PURPLE = SOFT RECOMENDATIONS

2023-24' 250/300 Race Edition

250/300 Race Edition Fork Adjustment

Fork Spring Rate .45 kg Oil level 300 cc Pressure spring Rate 2.1 kg Compression = 14 out 10 14 16 Rebound = 14 out 12 14 16

250/300 Race Shock Adjustment

Shock Spring Rate 5.3 kg
Static Sag Range 25-45mm
Rider Sag Range 95-110mm

Low Speed Compression = 13 out 7 12 15 High Speed Compression = 1.5 turns out 1.25 1.5 1.75 Rebound = 13 out 7 9 12

ADJUSTMENT KEY:

RED = FACTORY SETTINGS BLUE = RACING RECOMMENDATIONS GREEN = COMFORT RECOMMENDATIONS PURPLE = SOFT RECOMENDATIONS

2023-24' RX300

RX300 Fork Adjustment

Fork Spring Rate .44 kg Compression = 14 out 10 14 16
Oil level 300 cc Rebound = 14 out 12 14 16
Pressure spring Rate 2.1 kg

RX300 Shock Adjustment

Shock Spring Rate 5.3 kg Low Speed Compression = 14 out 8 12 16
Static Sag Range 25-45mm High Speed Compression = 1.5 turns out 1.25 1.5 1.75
Rider Sag Range 95-110mm Rebound = 14 out 12 14 16

.....

ADJUSTMENT KEY:

RED = FACTORY SETTINGS BLUE = RACING RECOMMENDATIONS GREEN = COMFORT RECOMMENDATIONS PURPLE = SOFT RECOMENDATIONS

2023-24' 350/390/430/480 Race Edition

350/390/430/480 Race Edition Fork Adjustment

Fork Spring Rate .48 kg Compression = 14 out 10 14 16
Oil level 300 cc Rebound = 14 out 12 14 16
Pressure spring Rate 2.1 kg

350/390/430/480 Race Shock Adjustment

Shock Spring Rate 5.5 kg Low Speed Compression = 13 out 7 12 15
Static Sag Range 25-45mm High Speed Compression = 1.5 turns out 1.25 1.5 1.75
Rider Sag Range 95-110mm Rebound = 13 out 7 9 12