

ENGINE

Type	Beta Built single cylinder, 2-stroke, liquid cooled, with BPV power valve system and counter balancer, electric start with back-up kick starter sold as an option
Bore	73mm
Stroke	69.9mm
Displacement	292.3cc
Compression Ratio	11.55:1
Exhaust Valve	Beta Progressive Valve (BPV)
Ignition	AC-CDI Kokusan
Spark Plug	NGK GR7CI8
Lubrication	Electronic Oil Injection
Oil Tank Capacity	650cc
Carburetor	Keihin PWK 36mm
Clutch	Wet Diaphragm-style
Transmission	6 Speed
Final Drive	O-ring chain

MSRP \$8,399.00

CHASSIS

Frame	Molybdenum steel / Parameter-style w/ quick air filter access
Wheelbase	57.8"
Seat Height	35.8"
Ground Clearance	12.6"
Footrest Height	15.4"
Dry Weight	218 lbs (wet weight, no fuel)
Fuel Tank Capacity	2.32 US Gallons
Front Suspension	43 mm inverted front fork with adjustable damping
Rear Suspension	Steel body shock with adjustable rebound and compression
Front Wheel Travel	10.6"
Rear Wheel Travel	10.6"
Front Brake	260 mm floating rotor
Rear Brake	240 mm rotor
Front/Rear Rim	21" (Front) 18" (Rear)
Front/Rear Tire	Soft Enduro Competition

*Specifications subject to change without notice. Additional information on all models including manuals, accessories, and parts books are available online at www.betausa.com under the support tab. **This model is for competition use only

