



2026 Suspension Spring Chart

(Springs rates listed in kilograms, or newton meter)

2026 Xtrainer **300RR** 2-Stroke

Olle' Fork: Stock - .80kg	-1" Lowering Kit AB- 41103	-2" Lowering Kit AB- 41104	Weight Range
Standard Travel 555mm Length	-1" Lowered 530mm Length	-2" Lowered 510mm Length	
.74 AB-12043-74	Custom Order	Custom Order	100-119 lbs.
.76 AB-12043-76	.76 AB-12077-76	.76 AB-12078-76	120-139 lbs.
.78 AB-12043-78	.78 AB-12077-78	.78 AB-12078-78	140-159 lbs.
.80 AB-12043-80	.80 AB-12077-80	.80 AB-12078-80	160-179 lbs.
.82 AB-12043-82	.82 AB-12077-82	.82 AB-12078-82	180-199 lbs.
.84 AB-12043-84	.84 AB-12077-84	.84 AB-12078-84	200-219 lbs.
.86 AB-12043-86	.86 AB-12077-86	.86 AB-12078-86	220-239 lbs.
.88 AB-12043-88	Custom Order	Custom Order	240-259 lbs.
.90 AB-12043-90	Custom Order	Custom Order	260-279 lbs.
.92 AB-12043-92	Custom Order	Custom Order	+280 lbs.

Olle' RV16 Shock: Stock – 5.2kg	-1" Lowering Kit AB- 41103	-2" Lowering Kit AB- 41104	Weight Range
Standard Travel 235mm Length	-1" Lowered 225mm Length	-2" Lowered 225mm Length	
4.6 AB-10148-46	4.6 AB-10148-46	4.6 AB-10148-46	100-119 lbs.
4.8 AB-10148-48	4.8 AB-10148-48	4.8 AB-10148-48	120-139 lbs.
5.0 AB-10148-50	5.0 AB-10148-50	5.0 AB-10148-50	140-159 lbs.
5.2 AB-10148-52	5.2 AB-10148-52	5.2 AB-10148-52	160-179 lbs.
5.4 AB-10148-54	5.4 AB-10148-54	5.4 AB-10148-54	180-199 lbs.
5.6 AB-10148-56	5.6 AB-10148-56	5.6 AB-10148-56	200-219 lbs.
5.8 AB-10148-58	5.8 AB-10148-58	5.8 AB-10148-58	220-239 lbs.
6.0 AB-10148-60	6.0 AB-10148-60	6.0 AB-10148-60	240-259 lbs.
6.2 AB-10148-62	6.2 AB-10148-62	6.2 AB-10148-62	260-279 lbs.
6.4 AB-10148-64	6.4 AB-10148-64	6.4 AB-10148-64	+280 lbs.

Red denotes stock spring rate

Stock OEM spring will install with standard, -1", -2" lowering
(Spring rates are subject to change with Beta Factory Modifications)

2026 X-Pro RR 125/200cc 2-Stroke

ZF SHC Fork: Stock - .80kg	-1" Lowering Kit AB- 41127	-2" Lowering Kit AB- 41128	Weight Range
<i>Standard Travel 515mm Length</i>	<i>-1" Lowered 490mm Length</i>	<i>-2" Lowered 475mm Length</i>	
.72 AB-12047-72	.72 AB-12087-72	.72 AB-12088-72	100-119 lbs.
.76 AB-12047-76	.76 AB-12087-76	.76 AB-12088-76	120-139 lbs.
.80 AB-12047-80	.80 AB-12087-80	.80 AB-12088-80	140-159 lbs.
.84 AB-12047-84	.84 AB-12087-84	.84 AB-12088-84	160-179 lbs.
.88 AB-12047-88	.88 AB-12087-88	.88 AB-12088-88	180-199 lbs.
.92 AB-12047-92	.92 AB-12087-92	.92 AB-12088-92	200-219 lbs.
.96 AB-12047-96	.96 AB-12087-96	.96 AB-12088-96	220-239 lbs.
1.00 AB-12047-100	1.00 AB-12087-100	1.00 AB-12088-100	240-259 lbs.
1.04 AB-12047-104	1.04 AB-12087-104	1.04 AB-12088-104	260-279 lbs.
1.08 AB-12047-108	1.08 AB-12087-108	1.08 AB-12088-108	280 + lbs.

ZF 46 Shock: Stock - 4.8kg	-1" Lowering Kit AB- 41127	-2" Lowering Kit AB- 41128	Weight Range
<i>Standard Travel 260mm Length</i>	<i>-1" Lowered 230mm Length</i>	<i>-2" Lowered 230mm Length</i>	
4.4 AB-10150-44	4.4 AB-10149-44	4.4 AB-10149-44	100-119 lbs.
4.6 AB-10150-46	4.6 AB-10149-46	4.6 AB-10149-46	120-139 lbs.
4.8 AB-10150-48	4.8 AB-10149-48	4.8 AB-10149-48	140-159 lbs.
5.0 AB-10150-50	5.0 AB-10149-50	5.0 AB-10149-50	160-179 lbs.
5.2 AB-10150-52	5.2 AB-10149-52	5.2 AB-10149-52	180-199 lbs.
5.4 AB-10150-54	5.4 AB-10149-54	5.4 AB-10149-54	200-219 lbs.
5.6 AB-10150-56	5.6 AB-10149-56	5.6 AB-10149-56	220-239 lbs.
5.8 AB-10150-58	5.8 AB-10149-58	5.8 AB-10149-58	240-259 lbs.
6.0 AB-10150-60	6.0 AB-10149-60	6.0 AB-10149-60	260-279 lbs.
6.2 AB-10150-62	6.2 AB-10149-62	6.2 AB-10149-62	280 + lbs.

*Red denotes stock spring rate. Spring rates are subject to change with Beta Factory modifications *

2026 X-Pro RR 250/300cc 2-Stroke

ZF SHC Fork: Stock - .84kg	-1" Lowering Kit AB- 41127	-2" Lowering Kit AB- 41128	Weight Range
<i>Standard Travel 515mm Length</i>	<i>-1" Lowered 490mm Length</i>	<i>-2" Lowered 475mm Length</i>	
.72 AB-12047-72	.72 AB-12087-72	.72 AB-12088-72	100-119 lbs.
.76 AB-12047-76	.76 AB-12087-76	.76 AB-12088-76	120-139 lbs.
.80 AB-12047-80	.80 AB-12087-80	.80 AB-12088-80	140-159 lbs.
.84 AB-12047-84	.84 AB-12087-84	.84 AB-12088-84	160-179 lbs.
.88 AB-12047-88	.88 AB-12087-88	.88 AB-12088-88	180-199 lbs.
.92 AB-12047-92	.92 AB-12087-92	.92 AB-12088-92	200-219 lbs.
.96 AB-12047-96	.96 AB-12087-96	.96 AB-12088-96	220-239 lbs.
1.00 AB-12047-100	1.00 AB-12087-100	1.00 AB-12088-100	240-259 lbs.
1.04 AB-12047-104	1.04 AB-12087-104	1.04 AB-12088-104	260-279 lbs.
1.08 AB-12047-108	1.08 AB-12087-108	1.08 AB-12088-108	280 + lbs.

ZF 46 Shock: Stock - 5.2kg	-1" Lowering Kit AB- 41127	-2" Lowering Kit AB- 41128	Weight Range
<i>Standard Travel 260mm Length</i>	<i>-1" Lowered 230mm Length</i>	<i>-2" Lowered 230mm Length</i>	
4.6 AB-10150-46	4.6 AB-10149-46	4.6 AB-10149-46	110-119 lbs.
4.8 AB-10150-48	4.8 AB-10149-48	4.8 AB-10149-48	120-139 lbs.
5.0 AB-10150-50	5.0 AB-10149-50	5.0 AB-10149-50	140-159 lbs.
5.2 AB-10150-52	5.2 AB-10149-52	5.2 AB-10149-52	160-179 lbs.
5.4 AB-10150-54	5.4 AB-10149-54	5.4 AB-10149-54	180-199 lbs.
5.6 AB-10150-56	5.6 AB-10149-56	5.6 AB-10149-56	200-219 lbs.
5.8 AB-10150-58	5.8 AB-10149-58	5.8 AB-10149-58	220-239 lbs.
6.0 AB-10150-60	6.0 AB-10149-60	6.0 AB-10149-60	240-259 lbs.
6.2 AB-10150-62	6.2 AB-10149-62	6.2 AB-10149-62	260-279 lbs.
6.4 AB-10150-64	6.4 AB-10149-64	6.4 AB-10149-64	280 + lbs.

Red denotes stock spring rate Spring rates are subject to change with Beta Factory modifications

2026 X-Pro RR **350/390/430/480** 4-Stroke

ZF SHC Front: Stock - .48 kg	-1" Lowering Kit AB- 41127	-2" Lowering Kit AB- 41128	Weight Range
Standard Travel 515mm Length	-1" Lowered 490mm Length	-2" Lowered 475mm Length	
.84 AB-12047-84	.84 AB-12087-84	.84 AB-12088-84	100-119 lbs.
.88 AB-12047-88	.88 AB-12087-88	.88 AB-12088-88	120-139 lbs.
.92 AB-12047-92	.92 AB-12087-92	.92 AB-12088-92	140-159 lbs.
.96 AB-12047-96	.96 AB-12087-96	.96 AB-12088-96	160-179 lbs.
1.00 AB-12047-100	1.00 AB-12087-100	1.00 AB-12088-100	180-199 lbs.
1.04 AB-12047-104	1.04 AB-12087-104	1.04 AB-12088-104	200-219 lbs.
1.08 AB-12047-108	1.08 AB-12087-108	1.08 AB-12088-108	220-239 lbs.
1.12 AB-12047-112	Custom Order	1.12 AB-12088-112	240-259 lbs.
1.16 AB-12047-116	Custom Order	Custom Order	260-279 lbs.
Custom Order	Custom Order	Custom Order	280 + lbs.

ZF 46 Rear: Stock - 5.4 kg	-1" Lowering Kit AB- 41127	-2" Lowering Kit AB- 41128	Weight Range
Standard Travel 260mm Length	-1" Lowered 230mm Length	-2" Lowered 230mm Length	
4.8 AB-10150-48	4.8 AB-10149-48	4.8 AB-10149-48	100-119 lbs.
5.0 AB-10150-50	5.0 AB-10149-50	5.0 AB-10149-50	120-139 lbs.
5.2 AB-10150-52	5.2 AB-10149-52	5.2 AB-10149-52	140-159 lbs.
5.4 AB-10150-54	5.4 AB-10149-54	5.4 AB-10149-54	160-179 lbs.
5.6 AB-10150-56	5.6 AB-10149-56	5.6 AB-10149-56	180-199 lbs.
5.8 AB-10150-58	5.8 AB-10149-58	5.8 AB-10149-58	200-219 lbs.
6.0 AB-10150-60	6.0 AB-10149-60	6.0 AB-10149-60	220-239 lbs.
6.2 AB-10150-62	6.2 AB-10149-62	6.2 AB-10149-62	240-259 lbs.
6.4 AB-10150-64	6.4 AB-10149-64	6.4 AB-10149-64	260-279 lbs.
6.6 AB-10150-66	6.6 AB-10149-66	6.6 AB-10149-66	280-299 lbs.
6.8 AB-10150-68	Custom Order	Custom Order	300 + lbs.

Red denotes stock spring rate Spring rates are subject to change with Beta Factory Modifications

2026 RR Race Edition **125/200** 2-Stroke

KYB AOS Forks Stock Rate 4,1 N/m = .42 kg	1" Lowering Kit AB- 41115	-2" Lowering Kit AB- 41116	Weight Range
Standard Travel 497mm Length	1" Spring Series 470mm Length	-2" Spring Series 455mm Length	
.36 AB-12054-36	.36 AB-12086-36	Custom Order	100-119 lbs.
.38 AB-12054-38	.38 AB-12086-38	.38 AB-12053-38	120-139 lbs.
.40 AB-12054-40	.40 AB-12086-40	.40 AB-12053-40	140-159 lbs.
.42 AB-12054-42	.42 AB-12086-42	.42 AB-12053-42	160-179 lbs.
.44 AB-12054-44	.44 AB-12086-44	.44 AB-12053-44	180-199 lbs.
.46 AB-12054-46	.46 AB-12086-46	.46 AB-12053-46	200-219 lbs.
.48 AB-12054-48	.48 AB-12086-48	.48 AB-12053-48	220-239 lbs.
.50 AB-12054-50	.50 AB-12086-50	.50 AB-12053-50	240-259 lbs.
.52 AB-12054-52	.52 AB-12086-52	.52 AB-12053-52	260-279 lbs.
.54 AB-12054-54	.54 AB-12086-54	.54 AB-12053-54	+280 lbs.

46mm KYB Shock Stock Rate 4,8 N/m = 4.9 kg	1" Lowering Kit AB- 41115	-2" Lowering Kit AB- 41116	Weight Range
Standard Travel 250mm Length	1" Spring Series 270mm Length	-2" Spring Series 270mm Length	
4.4 AB-10155-44	4.4 AB-10155-44	4.4 AB-10155-44	100-119 lbs.
4.6 AB-10155-46	4.6 AB-10155-46	4.6 AB-10155-46	120-139 lbs.
4.8 AB-10155-48	4.8 AB-10155-48	4.8 AB-10155-48	140-159 lbs.
5.0 AB-10155-50	5.0 AB-10155-50	5.0 AB-10155-50	160-179 lbs.
5.2 AB-10155-52	5.2 AB-10155-52	5.2 AB-10155-52	180-199 lbs.
5.4 AB-10155-54	5.4 AB-10155-54	5.4 AB-10155-54	200-219 lbs.
5.6 AB-10155-56	5.6 AB-10155-56	5.6 AB-10155-56	220-239 lbs.
5.8 AB-10155-58	5.8 AB-10155-58	5.8 AB-10155-58	240-259 lbs.
6.0 AB-10155-60	6.0 AB-10155-60	6.0 AB-10155-60	260-279 lbs.
6.2 AB-10155-62	6.2 AB-10155-62	6.2 AB-10155-62	+280 lbs.

Red denotes stock spring rate Shock springs sold are aftermarket and +20mm longer than OEM
Spring rates are subject to change with Beta Factory Modifications

2026 RR Race Edition **250/300** 2-Stroke

KYB AOS Forks Stock Rate 4,4 N/m = .45 kg	-1" Lowering Kit AB- 41115	-2" Lowering Kit AB- 41116	Weight Range
Standard Travel 497mm Length	1" Spring Series 470mm Length	-2" Spring Series 455mm Length	
.38 AB-12054-38	.38 AB-12086-38	.38 AB-12053-38	100-119 lbs.
.40 AB-12054-40	.40 AB-12086-40	.40 AB-12053-40	120-139 lbs.
.42 AB-12054-42	.42 AB-12086-42	.42 AB-12053-42	140-159 lbs.
.44 AB-12054-44	.44 AB-12086-44	.44 AB-12053-44	160-179 lbs.
.46 AB-12054-46	.46 AB-12086-46	.46 AB-12053-46	180-199 lbs.
.48 AB-12054-48	.48 AB-12086-48	.48 AB-12053-48	200-219 lbs.
.50 AB-12054-50	.50 AB-12086-50	.50 AB-12053-50	220-239 lbs.
.52 AB-12054-52	.52 AB-12086-52	.52 AB-12053-52	240-259 lbs.
.54 AB-12054-54	.54 AB-12086-54	.54 AB-12053-54	260-279 lbs.
.56 AB-12054-56	.54 AB-12086-54	.54 AB-12053-54	+280 lbs.

46mm KYB Shock Stock Rate 5,2 N/m = 5.3 kg	-1" Lowering Kit AB- 41115	-2" Lowering Kit AB- 41116	Weight Range
Standard Travel 250mm Length	-1" Shock Series 270mm Length	-2" Shock Series 270mm Length	
4.6 AB-10155-46	4.6 AB-10155-46	4.6 AB-10155-46	100-119 lbs.
4.8 AB-10155-48	4.8 AB-10155-48	4.8 AB-10155-48	120-139 lbs.
5.0 AB-10155-50	5.0 AB-10155-50	5.0 AB-10155-50	140-159 lbs.
5.2 AB-10155-52	5.2 AB-10155-52	5.2 AB-10155-52	160-179 lbs.
5.4 AB-10155-54	5.4 AB-10155-54	5.4 AB-10155-54	180-199 lbs.
5.6 AB-10155-56	5.6 AB-10155-56	5.6 AB-10155-56	200-219 lbs.
5.8 AB-10155-58	5.8 AB-10155-58	5.8 AB-10155-58	220-239 lbs.
6.0 AB-10155-60	6.0 AB-10155-60	6.0 AB-10155-60	240-259 lbs.
6.2 AB-10155-62	6.2 AB-10155-62	6.2 AB-10155-62	260-279 lbs.
6.4 AB-10155-64	6.4 AB-10155-64	6.4 AB-10155-64	+280 lbs.

***Red denotes stock spring rate* Shock springs sold are aftermarket and +20mm longer than OEM
Spring rates are subject to change with Beta Factory Modifications**

2026 RR Race Edition **350/390/430/480** 4-Stroke

KYB AOS Forks Stock Rate 4,7 N/m = .48 kg	1" Lowering Kit AB- 41115	2" Lowering Kit AB- 41116	Weight Range
Standard Travel 497mm Length	1" Spring Series 470mm Length	2" Spring Series 455mm Length	
.42 AB-12054-42	.42 AB-12086-42	.42 AB-12053-42	100-119 lbs.
.44 AB-12054-44	.44 AB-12086-44	.44 AB-12053-44	120-139 lbs.
.46 AB-12054-46	.46 AB-12086-46	.46 AB-12053-46	140-159 lbs.
.48 AB-12054-48	.48 AB-12086-48	.48 AB-12053-48	160-179 lbs.
.50 AB-12054-50	.50 AB-12086-50	.50 AB-12053-50	180-199 lbs.
.52 AB-12054-52	.52 AB-12086-52	.52 AB-12053-52	200-219 lbs.
.54 AB-12054-54	.54 AB-12086-54	.54 AB-12053-54	220-239 lbs.
.56 AB-12054-56	.56 AB-12086-56	.56 AB-12053-56	240-259 lbs.
.58 AB-12054-58	.58 AB-12086-58	.58 AB-12053-58	260-279 lbs.
Custom Order	Custom Order	Customer Order	+280 lbs.

46mm KYB Shock Stock Rate 5,4 N/m = 5.5 kg	1" Lowering Kit AB- 41115	2" Lowering Kit AB- 41116	Weight Range
Standard Travel 250mm Length	1" Shock Series 270mm Length	2" Shock Series 270mm Length	
4.8 AB-10155-48	4.8 AB-10155-48	4.8 AB-10155-48	100-119 lbs.
5.0 AB-10155-50	5.0 AB-10155-50	5.0 AB-10155-50	120-139 lbs.
5.2 AB-10155-52	5.2 AB-10155-52	5.2 AB-10155-52	140-159 lbs.
5.4 AB-10155-54	5.4 AB-10155-54	5.4 AB-10155-54	160-179 lbs.
5.6 AB-10155-56	5.6 AB-10155-56	5.6 AB-10155-56	180-199 lbs.
5.8 AB-10155-58	5.8 AB-10155-58	5.8 AB-10155-58	200-219 lbs.
6.0 AB-10155-60	6.0 AB-10155-60	6.0 AB-10155-60	220-239 lbs.
6.2 AB-10155-62	6.2 AB-10155-62	6.2 AB-10155-62	240-259 lbs.
6.4 AB-10155-64	6.4 AB-10155-64	6.4 AB-10155-64	260-279 lbs.
6.6 AB-10155-66	6.6 AB-10155-66	6.6 AB-10155-66	+280 lbs.

Red denotes stock spring rate Shock springs sold are aftermarket and 20mm longer than OEM
Spring rates are subject to change with Beta Factory Modifications

2026 BETA 250/350 RX 2-Stroke

KYB AOS Fork:	250/350 RX
Stock Rate: 4,4 N/mm = .45 KG	Fork Spring Length 497mm
.38 AB-12054-38	100-119 lbs.
.40 AB-12054-40	120-139 lbs.
.42 AB-12054-42	140-159 lbs.
.44 AB-12054-44	160-179 lbs.
.46 AB-12054-46	180-199 lbs.
.48 AB-12054-48	200-219 lbs.
.50 AB-12054-50	220-239 lbs.
.52 AB-12054-52	240-259 lbs.
.54 AB-12054-54	260-279 lbs.
.56 AB-12054-56	+280 lbs.

50mm KYB Shock:	250/350 RX
Stock Rate: 5,2 N/m = 5.3 kg	Shock Spring Length 250mm
4.7 AB-10156-47	100-119 lbs.
4.9 AB-10156-49	120-139 lbs.
5.1 AB-10156-51	140-159 lbs.
5.3 AB-10156-53	160-179 lbs.
5.5 AB-10156-55	180-199 lbs.
5.7 AB-10156-57	200-219 lbs.
5.9 AB-10156-59	220-239 lbs.
6.1 AB-10156-61	240-259 lbs.
6.3 AB-10156-63	260-279 lbs.
6.6 AB-10156-66	+280 lbs.

Red denotes stock spring rate

Shock disassembly required for Xtrig PLA

Suspension lowering for RX models is not available

(Spring rates are subject to change with Beta Factory Modifications)

2026 BETA 450 RX 4-Stroke

KYB AOS Fork:	450 RX
Stock Rate: 4,9 N/m = .50 kg	Fork Spring Length 497mm
.44 AB-12054-44	100-119 lbs.
.46 AB-12054-46	120-139 lbs.
.48 AB-12054-48	140-159 lbs.
.50 AB-12054-50	160-179 lbs.
.52 AB-12054-52	180-199 lbs.
.54 AB-12054-54	200-219 lbs.
.56 AB-12054-56	220-239 lbs.
.58 AB-12054-58	240-259 lbs.
.60 AB-12054-60	260-279 lbs.

50mm KYB Shock:	450 RX
Stock Rate: 5,4 N/m = 5.5 kg	Shock Spring Length 250mm
4.9 AB-10156-49	100-119 lbs.
5.1 AB-10156-51	120-139 lbs.
5.3 AB-10156-53	140-159 lbs.
5.5 AB-10156-55	160-179 lbs.
5.7 AB-10156-57	180-199 lbs.
5.9 AB-10156-59	200-219 lbs.
6.1 AB-10156-61	220-239 lbs.
6.3 AB-10156-63	240-259 lbs.
6.6 AB-10156-66	260-279 lbs.
6.8 AB-10156-68	+280 lbs.

Red denotes stock spring rate

Shock disassembly required for Xtrig PLA

Suspension lowering for RX models is not available

(Spring rates are subject to change with Beta Factory Modifications)

2026 RRS 350/390/430/480 4-Stroke

ZF Sachs Fork: Stock - .48kg	-1" Lowering Kit AB- 41106	-2" Lowering Kit AB- 41107	Weight Range
Standard Travel 460mm Length	-1" Lowered 435mm Length	-2" Lowered 420mm Length	
.42 AB-12048-42	.42 AB-12080-42	.42 AB-12081-42	100-119 lbs.
.44 AB-12048-44	.44 AB-12080-44	.44 AB-12081-44	120-139 lbs.
.46 AB-12048-46	.46 AB-12080-46	.46 AB-12081-46	140-159 lbs.
.48 AB-12048-48	.48 AB-12080-48	.48 AB-12081-48	160-179 lbs.
.50 AB-12048-50	.50 AB-12080-50	.50 AB-12081-50	180-199 lbs.
.52 AB-12048-52	.52 AB-12080-52	.52 AB-12081-52	200-219 lbs.
.54 AB-12048-54	.54 AB-12080-54	.54 AB-12081-54	220-239 lbs.
.56 AB-12048-56	Custom Order	.56 AB-12081-56	240-259 lbs.
.58 AB-12048-58	Custom Order	Custom Order	260-279 lbs.
Custom Order	Custom Order	Custom Order	280 + lbs.
ZF 46 Shock: Stock – 5.4kg	-1" Lowering Kit AB- 41106	-2" Lowering Kit AB- 41107	Weight Range
Standard Travel 260mm Length	-1" Lowered 230mm Length	-2" Lowered 230mm Length	
4.8 AB-10150-48	4.8 AB-10149-48	4.8 AB-10149-48	100-119 lbs.
5.0 AB-10150-50	5.0 AB-10149-50	5.0 AB-10149-50	120-139 lbs.
5.2 AB-10150-52	5.2 AB-10149-52	5.2 AB-10149-52	140-159 lbs.
5.4 AB-10150-54	5.4 AB-10149-54	5.4 AB-10149-54	160-179 lbs.
5.6 AB-10150-56	5.6 AB-10149-56	5.6 AB-10149-56	180-199 lbs.
5.8 AB-10150-58	5.8 AB-10149-58	5.8 AB-10149-58	200-219 lbs.
6.0 AB-10150-60	6.0 AB-10149-60	6.0 AB-10149-60	220-239 lbs.
6.2 AB-10150-62	6.2 AB-10149-62	6.2 AB-10149-62	240-259 lbs.
6.4 AB-10150-64	6.4 AB-10149-64	6.4 AB-10149-64	260-279 lbs.
6.6 AB-10150-66	6.6 AB-10149-66	6.6 AB-10149-66	280-299 lbs.
6.8 AB-10150-68	Custom Order	Custom Order	300 + lbs.

* Red denotes stock spring rate. Spring rates are subject to change with Beta Factory modifications.

2026 EVO Standard, Cincro & Factory Edition Trials models

Olle' Fork:	Standard Model	Tbd:	Cincro Model	Tbd:	Factory Edition
.78 (Stock)	160-179 lbs.		160-179 lbs.		160-179 lbs.
.80 AB-xxxxxx	175-199 lbs.		175-199 lbs.		175-199 lbs.
.84 AB-xxxxxx	200-229 lbs.		200-229 lbs.		200-229 lbs.
.88 AB-xxxxxx	230-249 lbs.		230-249 lbs.		230-249 lbs.
.92 AB-xxxxxx	250-269 lbs.		250-269 lbs.		250-269 lbs.
.94 AB-xxxxxx	270-300 lbs.		270-300 lbs.		270-300 lbs.

Olle' RV16 Shock:	Standard Model	Tbd:	Cincro Model	Tbd:	Factory Edition
7.1 kg (Stock)	160-179 lbs.		160-179 lbs.		160-179 lbs.
7.4 AB-xxxxxx	170-189 lbs.		170-189 lbs.		170-189 lbs.
7.6 AB-xxxxxx	190-209 lbs.		190-209 lbs.		190-209 lbs.
7.8 AB-xxxxxx	210-229 lbs.		210-229 lbs.		210-229 lbs.
8.0 AB-xxxxxx	230-249 lbs.		230-249 lbs.		230-249 lbs.
8.2 AB-xxxxxx	250-269 lbs.		250-269 lbs.		250-269 lbs.
8.4 AB-xxxxxx	270-289 lbs.		270-289 lbs.		270-289 lbs.
8.6 AB-xxxxxx	266-290 lbs.		266-290 lbs.		266-290 lbs.

Red denotes stock spring rate

Beta Factory XT-R Performance Suspension

Model: 2016-26' Xtrainer **250/300RR**

ZF 48 Forks:			Weight Range
<i>XT-R Std. Travel</i>	<i>XT-R -1" Lowered</i>	<i>XT-R -2" Lowered</i>	
.36 AB-12081-36	.36 AB-12084-36	.36 AB-12085-36	110-119 lbs.
.38 AB-12081-38	.38 AB-12084-38	.38 AB-12085-38	120-139 lbs.
.40 AB-12081-40	.40 AB-12084-40	.40 AB-12085-40	140-159 lbs.
.42 AB-12081-42	.42 AB-12084-42	.42 AB-12085-42	160-179 lbs.
.44 AB-12081-44	.44 AB-12084-44	.44 AB-12085-44	180-199 lbs.
.46 AB-12081-46	.46 AB-12084-46	.46 AB-12085-46	200-219 lbs.
.48 AB-12081-48	.48 AB-12084-48	.48 AB-12085-48	220-239 lbs.
.50 AB-12081-50	.50 AB-12084-50	.50 AB-12085-50	240-259 lbs.
.52 AB-12081-52	.52 AB-12084-52	.52 AB-12085-52	260-279 lbs.
.54 AB-12081-54	.54 AB-12084-54	.54 AB-12085-54	280 + lbs.

ZF 46 Shock:			Weight Range
<i>XT-R Std. Travel</i>	<i>XT-R 1" Lowered</i>	<i>XT-R -2" Lowered</i>	
4.6 AB-10149-46	4.6 AB-10149-46	4.6 AB-10153-46	110-119 lbs.
4.8 AB-10149-48	4.8 AB-10149-48	4.8 AB-10153-48	120-139 lbs.
5.0 AB-10149-50	5.0 AB-10149-50	5.0 AB-10153-50	140-159 lbs.
5.2 AB-10149-52	5.2 AB-10149-52	5.2 AB-10153-52	160-179 lbs.
5.4 AB-10149-54	5.4 AB-10149-54	5.4 AB-10153-54	180-199 lbs.
5.6 AB-10149-56	5.6 AB-10149-56	5.6 AB-10153-56	200-219 lbs.
5.8 AB-10149-58	5.8 AB-10149-58	5.8 AB-10153-58	220-239 lbs.
6.0 AB-10149-60	6.0 AB-10149-60	6.0 AB-10153-60	240-259 lbs.
6.2 AB-10149-62	6.2 AB-10149-62	6.2 AB-10153-62	260-279 lbs.
6.4 AB-10149-64	6.4 AB-10149-64	6.4 AB-10153-64	280 + lbs.

Red denotes stock spring rate.

Spring rates are subject to change with Beta Factory Modifications

OHLINS RXF 48 / TTX 46 FLOW DV Suspension

RXF 48 Fork Set:	TTX 22	2-Stroke	4-Stroke
Installed spring 4,3 N/m = .44kg	Closed Cartridge Assembly		
AB-42005-40	AB-42003-40	120-139 lbs.	
AB-42005-42	AB-42003-42	140-159 lbs.	120-139 lbs.
AB-42005-44	AB-42003-44	160-179 lbs.	140-159 lbs.
AB-42005-46	AB-42003-46	180-199 lbs.	160-179 lbs.
AB-42005-48	AB-42003-48	200-219 lbs.	180-199 lbs.
AB-42005-52	AB-42003-52	220-239 lbs.	200-219 lbs.
AB-42005-54	AB-42005-54	240-259 lbs.	220-239 lbs.
		260-279 lbs.	240-259 lbs.
			260-279 lbs.

TTX 46 Shock:	2-Stroke	4-Stroke
AB-42004-46	100-119 lbs.	
AB-42004-48	120-139 lbs.	100-119 lbs.
AB-42004-50	140-159 lbs.	120-139 lbs.
AB-42004-52	160-179 lbs.	140-159 lbs.
AB-42004-54	180-199 lbs.	160-179 lbs.
AB-42004-56	200-219 lbs.	180-199 lbs.
AB-42004-58	220-239 lbs.	200-219 lbs.
AB-42004-60	240-259 lbs.	220-239 lbs.
AB-42004-62	260-279 lbs.	240-259 lbs.
AB-42004-64		260-279 lbs.