



## 2022 - 300 RX Specifications

### ENGINE

Type	Beta Built single cylinder, 2-stroke, liquid cooled, with BPV power valve system, and electric start with a back-up kick starter sold as an option
Bore	72mm
Stroke	72mm
Displacement	293.1cc
Compression Ratio	11.63:1
Exhaust Valve	Beta Progressive Valve (BPV)
Ignition	AC-CDI Kokusan
Spark Plug	NGK BR8ECM
Lubrication	Premix
Oil Tank Capacity	N/A
Carburetor	Keihin PXX 38mm
Clutch	Wet Diaphragm-Style
Transmission	6 Speed
Final Drive	O-ring chain

**MSRP \$9,199.00**

### CHASSIS

Frame	Molybdenum steel / Double Cradle w/ quick air filter access
Wheelbase	58.6"
Seat Height	37"
Ground Clearance	13.3"
Footrest Height	16.9"
Dry Weight	220 lbs (wet weight, no fuel)
Fuel Tank Capacity	2.51 US Gallons
Front Suspension	48 mm KYB closed cartridge fork, adjustable compression & rebound
Rear Suspension	Aluminum Body Sachs shock w/adjustable rebound and hi/low speed compression
Front Wheel Travel	12.0"
Rear Wheel Travel	11.8"
Front Brake	260 mm floating rotor
Rear Brake	240 mm rotor
Front/Rear Rim	21" (Front) 19" (Rear)
Front/Rear Tire	Michelin Starcross
Warranty	6 Months Limited Warranty

\*Specifications subject to change without notice. Additional information on all models including manuals, accessories, and parts books are available online at [www.betausa.com](http://www.betausa.com) under the support tab.

