



## 2022 - EVO 80 Sr 2-Stroke Specifications

### ENGINE

Type	Single cylinder, 2-stroke, liquid-cooled with reed valve
Bore	48mm
Stroke	44mm
Displacement	79.6cc
Compression Ratio	14.7:1
Ignition	Electronic 12 Volt, 85 watt
Spark Plug	Champion RN3C
Lubrication	Pre-mix (synthetic oil)
Carburetor	Dell'Orto 21mm
Clutch	Wet multi-disc
Transmission	Six Speed
Warranty	6 Months Limited Warranty

**MSRP**      **TBD**

### CHASSIS

Frame	Steel frame with engine as support
Wheelbase	48.4"
Seat Height	26"
Ground Clearance	12.8"
Footrest Height	14.7"
Dry Weight	145.5 lbs (dry weight)
Fuel Tank Capacity	.7 US Gallons
Front Suspension	38mm Paioli
Rear Suspension	Adjustable single shock, aluminum bodied, with nitrogen, including linkage
Front wheel travel	6.9"
Rear wheel travel	5.9"
Final Gearing	11t front, 60t rear
Front brake	185mm rotor w/ 4-piston caliper
Rear brake	160mm rotor w/ twin-piston caliper
Front/Rear Rim	21" (Front) 18" (Rear)
Front/Rear Tire	Michelin Trial

\*Specifications subject to change without notice. Additional information on all models including manuals, accessories, and parts books are available online at [www.betausa.com](http://www.betausa.com) under the support tab.

