

ENGINE

Type	Single cylinder, 2-stroke, liquid-cooled with reed valve
Bore	84mm
Stroke	53.6mm
Displacement	297.3cc
Compression Ratio	10.5:1
Ignition	Electronic 12 Volt, 85 watt w/ dual-map switch (aggressive or soft settings)
Spark Plug	NGK MR7BI8 IR
Lubrication	Internal oil pump w/ cartridge filter
Carburetor	Mikuni CV
Clutch	Wet multi-disc w/ cush-drive basket
Transmission	Five Speed
Warranty	6 Months Limited Warranty

MSRP \$8,999.00**CHASSIS**

Frame	Aluminum beam, single wave Hydro-Formed w/ built in tank
Wheelbase	51.4"
Seat Height	26"
Ground Clearance	12.2"
Footrest Height	13.6"
Dry Weight	155.5 lbs (dry weight)
Fuel Tank Capacity	.75 US Gallons
Front Suspension	38mm w/ adjustable compression and rebound
Rear Suspension	Adjustable single shock, aluminum bodied, with nitrogen, including linkage
Front wheel travel	6.5"
Rear wheel travel	7.1"
Final Gearing	11t front, 42t rear
Front brake	185mm rotor w/ 4-piston caliper
Rear brake	160mm rotor w/ twin-piston caliper
Front/Rear Rim	21" (Front) 18" (Rear)
Front/Rear Tire	Michelen XLite Trial

*Specifications subject to change without notice. Additional information on all models including manuals, accessories, and parts books are available online at www.betausa.com under the support tab.

