

ENGINE

Type	Beta Built single cylinder, 2-stroke, liquid cooled, with BPV power valve system and electric start with back-up kick starter sold as an option
Bore	62mm
Stroke	63mm
Displacement	190.2cc
Compression Ratio	13.5:1
Exhaust Valve	Beta Progressive Valve (BPV)
Ignition	AC-CDI Kokusan
Spark Plug	NGK BR8ECM
Lubrication	Pre-Mix
Oil Tank Capacity	N/A
Carburetor	Keihin PWK 36mm
Clutch	Wet mutli-disk
Transmission	6 Speed
Final Drive	O-ring chain

MSRP \$9,799.00

CHASSIS

Frame	Molybdenum steel / Double Cradle w/ quick air filter access
Wheelbase	58.1"
Seat Height	36.6"
Ground Clearance	12.8"
Footrest Height	16.1"
Dry Weight	211.5 lbs (wet weight, no fuel)
Fuel Tank Capacity	2.5 US Gallons
Front Suspension	48 mm KYB AOS closed cartridge fork, adjustable compression & rebound
Rear Suspension	KYB 46 mm body with adjustable rebound and high/low speed on compression adjustment
Front Wheel Travel	11.8"
Rear Wheel Travel	12.4"
Front Brake	260 mm floating rotor
Rear Brake	240 mm rotor
Front/Rear Rim	21" (Front) 18" (Rear)
Front/Rear Tire	Metzeler Six Day Off Road

*Specifications subject to change without notice
Additional information on all models including manuals, accessories, and parts books are available online at www.betausa.com under the support tab

**This model is for competition use only

