

2020 Evo 300 4 Stroke

Engine

Type: Single cylinder, 4-stroke, 4-valve, liquid-cooled

Bore: 84mm
Stroke: 53.6mm
Displacement: 297.3cc
Compression Ratio: 11.5:1

Ignition: Electronic 12 volt w/ dual-map switch (aggressive or soft settings)

Spark Plug: NGK MR7BI-8

Lubrication: Internal oil pump w/ cartridge filter

Carburetor: Mikuni CV
Clutch: Wet multi-disc
Transmission: 5-speed

Chassis

Frame: Aluminum beam, single wave Hydro-Formed w/built in fuel tank

Wheelbase: 51.4"
Seat Height: 26"
Ground Clearance: 12.2"
Footrest Height: 13.6"

Dry Weight: 155.5 lbs. dry Fuel Tank Capacity: .75 US gallons

Front Suspension: 38mm Paioli including hard-coated tubes

Rear Suspension: Adjustable single shock, aluminum bodied, including linkage

Front Wheel Travel: 6.5" Rear Wheel Travel: 7.1"

Final Gearing: 11t front, 42t rear

Front Brake: 185mm rotor w/ 4-piston caliper
Rear Brake: 160mm rotor w/ twin-piston caliper

Front/Rear Rim: 21" (Front) 18" (Rear)

Front/Rear Tire: Dunlop Trial

Warranty: 6 month Limited Warranty

MSRP: TBA

Additional information on all models including manuals, accessories and parts books are available online at BetaUSA.com under Support.



^{*}specifications subject to change without notice.