



Beta Radiator Braces Kit

Part# AB-21262

Fits: 2018+ Beta 125 RR 2-stroke

Installation Instructions:

The Beta Radiator Brace kit includes:

4 - side plates; outer left, inner left, inner right, outer right

4 - hat washers

8 - support rods

16 - 6mm button head allen screws

4 - 6mm radiator mount screws

2 - radiator louvres



1. Remove seat, shut off fuel petcock, remove fuel line from petcock, disconnect gas cap vent hose.
2. Remove two 8mm screws holding gas tank to the frame, & both 8mm screws holding radiator shrouds to the bottom of the radiators.
3. Fuel tank & shrouds can now be removed as one unit. Remove right & left radiator louvers from the radiators.
4. Install radiator brace support rods onto left & right inner guard plates (inner plates have large mount holes) with button head allen screws.
5. Tighten these 8 inner screws tightly as they won't be accessible after mounting.
6. Unscrew the 4 inner radiator mount screws from both radiators & the frame.
7. Pull the radiators away from the frame, rotating them slightly rearwards.
8. Slide inner half of guard plates onto left & right radiators & align mount holes.
9. Place the four 6mm screws through their 4 hat washers & install into radiators.
10. With radiator guard plates on the outside, mount them into frame mount holes.
11. Install outer right side plate using 6mm allen bolts, repeat the process for left side outer plate.
12. Recheck all four radiator mount screws, & all 16 outer plate mount screws.
13. Reinstall radiator front louvres, gas tank, seat, fuel line & vent hose.